

17360 : BASE 17369: CURING AGENT 97040

Description:	HEMPADUR ZINC 17360 is a two-component, zinc rich epoxy primer. It cures to a hard wearing and highly weather-resistant coating. Offers cathodic protection of local mechanical damage.
Recommended use:	As a "V.O.C.-compliant", versatile, long-term primer on steel for epoxy, vinyl and acrylic coating systems in medium to severely corrosive environments. In compliance with SSPC-Paint 20, type 2, level 2 and ISO 12944-5.
Service temperature:	Maximum, dry exposure only: 160°C/320°F
Certificates/Approvals:	Complies with EU Directive 2004/42/EC: subcategory j.
Availability:	Part of Group Assortment. Local availability subject to confirmation.

PHYSICAL CONSTANTS:

Shade nos/Colours:	19830* / Reddish grey
Finish:	Flat
Volume solids, %:	65 ± 1
Theoretical spreading rate:	13 m ² /l [521.3 sq.ft./US gallon] - 50 micron/2 mils
Flash point:	24 °C [75.2 °F]
Specific gravity:	2.8 kg/litre [23.1 lbs/US gallon]
Surface-dry:	15 minute(s) 20°C/68°F
Through-dry:	1.5 hour(s) 20°C/68°F
Fully cured:	7 day(s) 20°C/68°F
VOC content:	310 g/l [2.6 lbs/US gallon]
Shelf life:	1 year for BASE and 3 years (25°C/77°F) for CURING AGENT from time of production. <i>*other shades according to assortment list.</i>

The physical constants stated are nominal data according to the HEMPEL Group's approved formulas.

APPLICATION DETAILS:

Version, mixed product:	17360
Mixing ratio:	BASE 17369: CURING AGENT 97040 4 : 1 by volume
Application method:	Airless spray / Air spray / Brush
Thinner (max.vol.):	08450 (5%) / 08450 (15%) / 08450 (5%) see REMARKS overleaf
Pot life:	2 hour(s) 20°C/68°F
Nozzle orifice:	0.017 - 0.021 "
Nozzle pressure:	150 bar [2175 psi] (Airless spray data are indicative and subject to adjustment)
Cleaning of tools:	HEMPEL'S TOOL CLEANER 99610
Indicated film thickness, dry:	50 micron [2 mils] see REMARKS overleaf
Indicated film thickness, wet:	75 micron [3 mils]
Overcoat interval, min:	see REMARKS overleaf
Overcoat interval, max:	see REMARKS overleaf

Safety:	Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult HEMPEL Safety Data Sheets and follow all local or national safety regulations.
----------------	--

